

**TEKNISET TIEDOT**  
**TUTELA TRANSMISSION STARGEAR AX**  
**TUOTEKOODI:: 2292**

**SOVELTAMINEN**

Lubricant for axles of cars and commercial vehicles (especially the Mercedes) that allows for maximum protection of the mechanical parts during use at high temperatures and severe operating conditions.

The modern formulation ensures protection against wear, oxidation and rust.

The viscometric index allows rapid and safe lubrication during cold starts and during exercise at low temperatures.

**MÄÄRITYKSET**

SAE 85W-90, API GL 5, MB-Approval 235.0, RENAULT where API GL5 Recommended

ZF TE-ML 16C, ZF TE-ML 17B, ZF TE-ML 19B, ZF TE-ML 21A, MAN 342 Type\_M1 Performance, MIL-L-2105 D

**TESTIN KUVAUS**

TESTIN KUVAUS	MENETELMÄ	YKSIKKÖ	TYYPILLINEN ARVO
ULKONÄKÖ	--	--	B&C
VÄRI	--	--	AMBER
TIHEYS 15°C	ASTM D 4052	g/cm <sup>3</sup>	0.900
VISKOSITEETTI @ 100°C	ASTM D 445	cSt	17
VISKOSITEETTI @ 40°C	ASTM D 445	cSt	189
VISKOSITEETTI-INDEKSI	ASTM D 2270	--	95
VISKOSITEETTI @ -12°C	ASTM D 2983	cPs	31000
VIRTAUSPISTE	ASTM D 97	°C	-30
LEIMAHDUSPISTE CI. O. C.	ASTM D 92	°C	215
VAAHTO @ 24°C	ASTM D 892	cc/s	TRACES/0

Kaikki tekniset tiedot on annettu yksinomaan viitteeksi.